

Service Call:

Digger Derrick Hydraulic Oil
Specifications

Tools Required:

Unit Specific Maintenance Manual

Model(s):

All past and current production Terex
Digger Derricks

Tech Tip Safety Rules




Danger


Failure to obey the instructions and safety rules in the appropriate Operator's Manual and Service Manual for your machine will result in death or serious injury. Many of the hazards identified in the operator's manual are also safety hazards when maintenance and repair procedures are performed.

Do Not Perform Maintenance Unless:

- You are trained and qualified to perform maintenance on this machine.
- You read, understand and obey:
 - manufacturer's instructions and safety rules
 - employer's safety rules and worksite regulations
 - applicable governmental regulations
- You have the appropriate tools, lifting equipment and a suitable workshop.

The information contained in this tech tip is a supplement to the service manual. Consult the appropriate service manual of your machine for safety rules and hazards.

 **WARNING**



Escaping fluid under pressure can penetrate skin causing serious injury.

Relieve pressure before disconnecting hydraulic lines. Keep away from leaks and pin holes. Use a piece of cardboard or paper to search for leaks. Do not use your hand.

Fluid injected into skin must be surgically removed within a few hours by a doctor familiar with this type injury or gangrene will result.

H23877B

Introduction:

HYDRAULIC OIL SPECIFICATIONS

HYDRAULIC SYSTEM

Your hydraulic system has been engineered to give many years of useful service. A few simple rules and maintenance procedures are necessary to ensure efficient operation.

Hydraulic oil for your Digger Derrick must meet the following requirements listed below.

1. A petroleum based oil.
2. Anti-wear additives to ensure the long life of the hydraulic components.
3. Anti-foam additives to minimize air entrapment.
4. Good chemical stability at anticipated operating temperatures.
5. A flash point above anticipated operating temperatures.
6. Good demulsibility or water separation characteristics.
7. Dielectric strength.


Step 1

There are 2 possible ways to find and determine the proper hydraulic oil to use on a Digger Derrick. They are outlined in steps 2, 3, and 4 below. Always use the unit specific maintenance manual for the unit being repaired.

Step 2

Find “General Hydraulic System Maintenance” in Index of the unit specific maintenance manual.

SECTION 205205 - 1
GENERAL HYDRAULIC SYSTEM MAINTENANCE205 - 1
RETURN LINE FILTER REPLACEMENT205 - 2
TANK, BREATHER, FILLER AND OUTLET SCREENS205 - 3
CLEANLINESS205 - 3
HYDRAULIC TANK205 - 3
BREATHER205 - 3
HYDRAULIC TANK FILLER SCREEN205 - 4
HYDRAULIC TANK OUTLET SUCTION SCREEN FOR PUMP205 - 4
HYDRAULIC OIL SPECIFICATIONS205 - 5
HYDRAULIC SYSTEM205 - 5
OIL TYPE205 - 5
OPERATING TEMPERATURES205 - 6
VISCOSITY205 - 6
VISCOSITY INDEX205 - 6
ADDITIVES205 - 6
POUR POINT205 - 6
DIELECTRIC STRENGTH205 - 6
OIL STORAGE AND HANDLING205 - 7
GENERAL205 - 7



Step 3

Go to the “Hydraulic Oil Specifications” section.

Here you will find detailed information on selecting the proper hydraulic oil for the unit, as well as information on hydraulic oil system maintenance.

HYDRAULIC OIL SPECIFICATIONS	205 - 5
HYDRAULIC SYSTEM	205 - 5
OIL TYPE	205 - 5
OPERATING TEMPERATURES	205 - 6
VISCOSITY	205 - 6
VISCOSITY INDEX	205 - 6
ADDITIVES	205 - 6
POUR POINT	205 - 6
DIELECTRIC STRENGTH	205 - 6

Technical specifications of the correct type of oil to use can be found under “Oil Type”.

OIL TYPE

Oil used in the hydraulic system performs the dual function of lubrication and transmission of power. Oil must be selected with care and with the assistance of a reputable supplier.

Terex South Dakota, Inc. does not guarantee the quality or characteristics of any hydraulic oil for usage. A reputable distributor or supplier should be consulted in any hydraulic oil application. Mixing different oils or additives must be done only by the supplier. Serious damage to a hydraulic system can result from mixing incompatible hydraulic oils or additives.

	Contaminated fluid may cause damage to the pump and/or control valve. Before adding fluid to the system, be sure the fluid has been filtered through a 10-micron (absolute), or less, filter.
---	--


AMBIENT TEMP RANGE MIN. TO MAX.	ISO VISCOSITY GRADE	VISCOSITY INDEX
-40° To 120° F (-40° To 49° C)	15	140
32° To 120° F (0° To 49 ° C)	22	140

NOTE: Use 15 ISO max when equipped with top controls/radio controls.

Step 4

In the kit-sheets (parts section of manual or using online access-See tech Tip #50) under Final Assembly section is “Oil, Hydraulic, ISO 15” as an example. To the left of the description is our part number 419419. This kit-sheet will list the oil specifications. It will also list oils by manufacturer that meet specification.

Example from a C6000 series unit:

0465917	<u>FINAL ASSY. CTR. C6000</u>
0060099	<u>NYL ROPE LUG KIT (S/L)</u>
0419419	<u>OIL. HYDRAULIC. ISO 15</u> 
0420161	<u>WARNING DECALS (R/P USE 0424748P)</u>
0424748	<u>DECAL KIT (R/P USE 0424748P)</u>
0424749	<u>DECAL INSTALL INSTRUCTION</u>
0444443	<u>LOGO KIT (S/L) COMMANDER</u>
0444681	<u>LOGO INSTALL. DD</u>
0463277	<u>MAINTENANCE MANUAL, DIGGER DERRICK</u>
0463280	<u>OPERATORS MANUAL, DIGGER DERRICK</u>
0472262	<u>LEVEL INDICATOR. DD (S/L)</u>
0486277	<u>SLOPE INDICATOR</u>
0486451	<u>LEVEL INDICATOR INSTALL. DD</u>
0496291	<u>TEMPORARY CAP KIT</u>
0498829	<u>HAND SIGNAL CHART. (S/L)</u>
0498828	<u>INSTALL. OSHA HAND SIGNAL CHART</u>



ISO 15 Oil Specification:

OIL, HYDRAULIC- ISO 15		
DATE: 11/09/2016	ECN#: 73776	419419 H

OIL HYDRAULIC - ISO 15 SPECIFICATIONS

- 1) ISO VG RATING - 15
- 2) MINIMUM FLASH POINT - 280° F
- 3) MINIMUM POUR POINT - -40° F
- 4) MINIMUM V.I - 140
- 5) TYPICAL VISCOSITY RATING @ 100° F - (70 - 90 SUS)
- 6) TYPICAL VISCOSITY RATING @ 210° F - (39 - 43 SUS)
- 7) TYPICAL VISCOSITY RATING @ 0° F - (600 - 1300 SUS)
- 8) MINIMUM DIELECTRIC STRENGTH - 25 KV
- 9) TYPICAL API, GRAVITY RATING - (26 - 31)
- 10) DOES NOT REQUIRE CHARACTERISTICS OR RATING O.C. MIL. SPEC. 5606A.

SUGGESTED SUPPLIERS


- 1) MOBIL DTE - 11M
- 2) EXXON UNIVIS N15
- 3) TEXACO RANDO HDZ - 15HVI
- 4) PENZOIL AWX ARTIC 15
- 5) TEXACO RANDO POLAR ICE
- 6) KENDALL GLACIAL BLUE
- 7) NORTHLAND TALAMAR EXTREME LTT
- 8) AMERICAN SYNTHOL INC AMERILUBE PGHD 15 XLT
- 9) PETRO-CANADA HYDREX MV ARCTIC

* SEE SEPARATE ASSEMBLY SHEET

PAGE 1 OF 1

(NS) = NOT SHOWN

MIL-5606A Specification:

			
		OIL, HYDRAULIC - LOW TEMP	
DATE: 6/17/10	ECN# 55973	436396	D

OIL, HYDRAULIC - LOW TEMP SPECIFICATIONS

- 1) SIMILAR CHARACTERISTICS TO MIL. SPEC. 5606A
- 2) NOT REQUIRED TO MEET MIL. SPEC. 5606A.
- 3) MINIMUM FLASH POINT - 200° F
- 4) MINIMUM POUR POINT - -65° F OR LESS.
- 5) MINIMUM V.I. - 200.
- 6) TYPICAL VISCOSITY RATING @ 100° F - (70-90 SUS)
- 7) TYPICAL VISCOSITY RATING @ 210° F - (38-43 SUS)
- 8) MAXIMUM VISCOSITY RATING @ 0° F - (550 SUS)
- 9) TYPICAL API, GRAVITY RATING - (28-33)
- 10) MINIMUM DIELECTRIC STRENGTH - 25 KV

SUGGESTED SUPPLIERS

- 1) MOBIL AERO HFA(5606A RATED)
- 2) EXXON UNIVIS J-13(5606A RATED)
- 3) TEXACO AIRCRAFT HYD OIL #15(5606A RATED)
- 4) NORTHLAND GULFSTREAM AGHF
- 5) SHELL AERO SHELL #4(5606A RATED)
- 6) CHEVRON AVIATION HYD A(5606A RATED)
- AVIATION HYD C(5606A RATED)
- 7) BENZOIL HVI15
- 8) BP ENERGOL - SHF-LT15
- 9) PETRO-CANADA HYDREX MV. ARCTIC

* SEE SEPARATE ASSEMBLY SHEET PAGE 1 OF 1

(NS)=NOT SHOWN

Special note regarding oil selection and low temperatures:

The pour point listed in a manufacturer's specifications must be lower than the anticipated ambient temperature or the hydraulic system will need to be heated.

Symptoms of incorrect oil type

During cold weather:

1. Slow, sluggish, or loss of performance
2. Increased noise from pump
3. Inconsistent pressure adjustments

During hot weather:

1. Increase in oil leaks
2. Increased noise from pump
3. Increase in oil temperature
4. Slow, sluggish, or loss of performance

Consequences of incorrect oil type

During cold weather:

1. Cavitation of pump.
2. Decreased lifespan of pump.
3. Increased contamination passed through system components.

During hot weather:

1. Inadequate lubrication of pump.
2. Decreased lifespan of pump.
3. Increased contamination passed through system components.